

Description: **ROBINHOOD STAINLESS STEEL WALL CANOPY SOFT TOUCH CONTROL (BRIMSTONE 60 & BRIMSTONE 90)**

Model Numbers: **RHWC60X(60CM); RHWC90X(90CM)**

Typical Design



RHWC60X



RHWC90X

Features and benefits

- **Sealed Motor**
Fully sealed metal AC motor in weldless casing
- **Metal Fan**
Metal fan with Teflon finish to ensure smooth air flow
- **Soft Touch Control**
User friendly soft touch control ensures easy operation
- **Lower Noise Level**
Reduced noise level whilst still achieving a high level of extraction
- **Ducted or Recirculated**
This rangehood can be either ducted with an optional ducting kit or simply recirculated with the use of charcoal filters (CARBONFTLDEEU)

Specifications

Technical data:

AESTHETICS

RANGEHOOD TYPE	STAINLESS STEEL
CONTROL TYPE	BACK-LIT SOFT TOUCH CONTROL
FILTERS	RHWC60X: DECARATIVE SS/ALUMINIUM FILTER *2 PCS RHWC90X: 5 LAYERS ALUMINIUM FILTER *3 PCS
LIGHTS	2 * 2W LED

FUNCTIONALITY

POWER LEVELS	3
DUCTED OR RECIRCULATED	YES
DUCTING DIAMETER	150MM

MOTOR/ELECTRICAL

MOTOR	FULLY SEALED AC MOTOR
BLADES	TEFLON COATED METAL BLADES
VOLTAGE & FREQUENCY	240V/50Hz
TOTAL POWER CONSUMPTION	184W
MOTOR WATTAGE	180W
PLUG FITTED	YES, 10AMP

DIMENSIONS

	RHWC60X	RHWC90X
CHIMNEY SIZE (W*D*H)	300*300*400-760MM	300*300*400-760MM
PRODUCT SIZE (W*D*H)	595*455*445-805MM	895*455*445-805MM
PACKAGE SIZE (W*D*H)	655*530*530MM	955*530*530MM
GROSS/NET WEIGHT	19.0KG/17.5KG	24.0KG/19.0KG

Performance data:

Max Motor Performance	IEC 61591 Test Data	Air Flow (m ³ /hr)	Noise Level (dB)
1200 m ³ /hr	Power Level 1	520	46
	Power Level 2	633	51
	Power Level 3	819	55

New Zealand

Monaco Corporation Ltd
Telephone: (09) 415 6000
Facsimile: (09) 415 7400
Email: enquiries@robinhood.co.nz
www.robinhood.co.nz

Australia

Shiro Australia Pty Ltd
ABN 28 002 386 129
Telephone: 1800 648 556
Facsimile: 1800 628 577
Email: enquiries@robinhood.com.au
www.robinhood.com.au